

Cold Forging Press with Knuckle Link Motion

Specifications

MODEL	UNIT	HKLP-160	HKLP-250		HKLP-400		HKLP-650		HKLP-800		HKLP-1000		HKLP-1200	
		S.T	S.T	L.S	S.T	L.S	S.T	L.S	S.T	L.S	S.T	L.S	S.T	L.S
Capacity	Ton	160	250		400		650		800		1000		1200	
Rated Tonnage Point	mm	4	7		7		7		7		10		13	
Slide Stroke	mm	90	160	300	200	300	220	400	250	400	250	400	250	400
Stroke Per Minute	S.P.M	70	55	30	50	30	45	25	40	25	30	20	30	20
Die Height	mm	340	400	700	460	700	520	1000	600	1000	700	1000	700	1000
Slide Adjustment	mm	30	40		40		50		50		60		60	
Slide Area(LRxFB)	mm	500x350	600x400		700x500		800x700		1000x900		1000x900		1100x1000	
Bolster Area(LRxFB)	mm	500x400	600x500		700x600		800x700		1000x900		1000x900		1100x1000	
BKO Capacity	Ton	8	12		20		20		30		30		50	
BKO Stroke	mm	35	60	120	80	120	90	170	100	170	100	170	100	170
Main Motor	KwxP	15x4	30x4	40x4	37x4	55x4	45x4	75x4	75x4	90x4	75x4	110x4	132x4	132x4